Example Code:

M4 - 420 4 A - 0 0 0 1 1 - 000

FAMILY	MODEL	LENGTH	WINDING	MOUNT	SHAFT	BRAKE	CONNECTION	FEEDBACK	SPECIAL OPTIONS
M4	420	3	**A** (2500 rpm, 140V) **B** (3200 rpm, 140V) **C** (3600 rpm, 140V) **D** (3600 rpm, 140V)	**0. STANDARD** IMB14, (4) M10x19 on Ø149.2 (5.875")	**0. STANDARD** Ø 1 3/8" x 2.5" & Keyway	**0. STANDARD** (None)	**0.** (Pg13.5 Cable Gland)	**0. STANDARD** (None)	**000. STANDARD**
		4	**A** (1950 rpm, 140V) **B** (2400 rpm, 140V) **C** (3200 rpm, 140V) **E** (1400 rpm, 140V)	**1. IMB5 (SQ.)** (4) Ø10.5 thru' on Ø196.85 (7.75")	**1.** Ø24j6x50 & Keyway	**1. OPTION** (24V DC, 20Nm)	**1. Connectors** MS3102A-28-10P & MS3102A-20-33P	**1.** (Tacho, 19 V/krpm) **2.** (Tacho, 57 V/krpm) **3.** (Tacho, 38 V/krpm) **4.** (Tacho, 47 V/krpm) **5.** (Tacho, 3 V/krpm) **6.** (Tacho, 30 V/krpm) * Other Tach Voltage available on request	
		5	**A** (1550 rpm, 140V) **B** (1950 rpm, 140V) **C** (2600 rpm, 140V) **D** (3200 rpm, 140V)	**2. IMB5** (4) Ø12 thru' on Ø165 PCD		**2. OPTION** (90V DC, 20Nm)	**2. Junction Box** (x2)		
		6	**A** (1300 rpm, 140V) **B** (1600 rpm, 140V) **C** (2100 rpm, 140V) **D** (2800 rpm, 140V)			**3. OPTION** (115V AC, 20Nm)	**3. Terminal Box** (with terminals)		
		7	**A** (1100 rpm, 140V) **B** (1400 rpm, 140V) **C** (1850 rpm, 140V) **D** (2600 rpm, 140V)					**Flexmount Enc.** Differential with index (Hollow Shaft) **T** (Optical Enc., 1024 ppr) **V** (Optical Enc., 2048 ppr) * Other Optical Encoders available on request	
		8	**A** (975 rpm, 140V) **B** (1200 rpm, 140V) **C** (1600 rpm, 140V) **D** (2400 rpm, 140V)						
		9	**A** (875 rpm, 140V) **B** (1000 rpm, 140V) **C** (1400 rpm, 140V) **D** (2100 rpm, 140V)						
			** Other windings available	**Y. SPECIAL**	**Y. SPECIAL**	**Y. SPECIAL**	**Y. SPECIAL**	**Y. SPECIAL**	

CALLAN TECHNOLOGY

Callan Technology Ltd. Bay K, 12A/12B Shannon Industrial Estate, Shannon, Co. Clare, Ireland
Tel: +353 61 47 57 82 | Fax: +353 61 47 57 83 | Email: info@callantechnology.com